


## **Dear Partners:**


It's middle of Q2. Taiwan had water shortage in Q1. Fortunately, raining season is coming. Below is the update of new product, please contact with your sales window for more details. Summer season is near, please also review your order status for Q2~Q3 and release it early.

- 2.8" TFT with OGS (one glass solution) capacitive touch panel- Please check below two items for different design request.
- 1) Product with black mask as the tablet like.
- IC: Sitronix ST1624
- Multi touch with sliding function






- 2) CTP solution which can replace2.8" resistive touch solution.
- IC: Sitronix ST1530
- One point touch with sliding function





- Please discuss with customer and feedback the mechanical design of LCM FPC in order to evaluate the quote.
- 4.3" with OGS solution is under developing. Please check with our sales if you have inquiry.
- 7" OGS capacitive touch as cost effective solution
  Please refer to the following drawings for mechanical design reference. Touch panel controller IC: ESMT YL8132. 5 Points touch with sliding function.




CTP IC list ---Standard TFT with projected capacitive touch panel.
 Touch panel structure= G+G (Glass cover lens + Glass sensor) .

| Size(Inch) | Powertip Part No.     | Interface | TP support operation | TP LSI | TP Interface |  |
|------------|-----------------------|-----------|----------------------|--------|--------------|--|
| 3.5        | PH320240T023-series   | 24bitRGB  | 5pointsmultitouch    | FT5216 | I2C          |  |
| 4.3        | PH480272T-006- series | 24bitRGB  | 5pointsmultitouch    | FT5216 | I2C          |  |
| 7          | PH800480T-013- series | 24bitRGB  | 10pointsmultitouch   | FT5406 | I2C          |  |



 NPC1602-L in VA type, OLED-like, Part Number: NPC1602WRP-LWA-I. Please refer to the following as Electrical/Optical characteristics and mechanical drawings.

| Electrical / Optical Characteristics |        |            |       |       |            |                   |  |  |
|--------------------------------------|--------|------------|-------|-------|------------|-------------------|--|--|
| Item                                 | Symbol | Conditions | Min.  | Тур.  | Max.       | Unit              |  |  |
| Forward Voltage                      | VF     | IF= 40 mA  | -     | (3.5) | (4.0)      | ٧                 |  |  |
| Average Brightness (without LCD)     | IV     |            | (200) | (230) | <b>/</b> - | cd/m <sup>2</sup> |  |  |
| Wavelength<br>(Without LCD)          | λр     |            | (569) | (572) | (575)      | nm                |  |  |
| Color                                |        |            | White | 5//   |            |                   |  |  |



• Custom Tooling storage—Powertip will scrap the tooling without receiving PO within two years. If you need the tooling to be kept, please inform the project status. Thank you.