



NOTES:

- 1.LCD TYPE: TFT
- 2.LCD DISPLAY: Normally Black/Transmissive
- 3.The tolerance unless classified ±0.3mm
4. Insulating Tape; Electric Conduction cloth Tape
- 5.CN1 connector : I-PEX 20455-030E (0.5pitch ; 30pin) or equivalent.
CN2 connector : CviLux CI4406M1H00 (1.25pitch ; 6pin) or equivalent.

007				PART NO:	PH192120T001-ZHC
006				DRAWING NAME :	LMD-PH192120T001-ZHC
005				TITLE:	LCD MODULE DRAWING
004					
003					
002	Modify Drawing	Jason	2023/08/17		
001	NEW DRAWING	Jason	2023/03/23		
REV	REV BY	REVISER	DATE		

		<p>久正光電股份有限公司 POWERTIP TECHNOLOGY CORPORATION</p>														
Design	Jason	(3)	Surface	<table border="1"> <thead> <tr> <th>Tolerance Length(Min) (mm)</th> <th>Precision Level</th> </tr> </thead> <tbody> <tr> <td>1 ~ 4</td> <td>-</td> </tr> <tr> <td>4 ~ 16</td> <td>-</td> </tr> <tr> <td>16 ~ 63</td> <td>-</td> </tr> <tr> <td>63 ~ 250</td> <td>-</td> </tr> <tr> <td>250 ~ 1000</td> <td>-</td> </tr> </tbody> </table>	Tolerance Length(Min) (mm)	Precision Level	1 ~ 4	-	4 ~ 16	-	16 ~ 63	-	63 ~ 250	-	250 ~ 1000	-
Tolerance Length(Min) (mm)	Precision Level															
1 ~ 4	-															
4 ~ 16	-															
16 ~ 63	-															
63 ~ 250	-															
250 ~ 1000	-															
Check	Tina	Unit	MM													
Approve	Bright	Scale	1:1													
		Page	1/1													
		Material														
		Thickness														
		Quantity														