


NOTE:

1. LCD TYPE: White.FSTN,Transflective,Positive.
2. LCD Module: 1/64duty, 1/9bias.
3. Viewing Direction: 6 O'clock.
4. Top: -20 TO 70°C,Tst: -30 TO 80°C.
5. The tolerance unless classified: ±0.3mm
6. This product conforms ROHS.

007				PART NO:		 久正光電股份有限公司 POWER TIP TECHNOLOGY CORPORATION				<table border="1"> <tr> <th colspan="2">公差精度</th> <th rowspan="2">精級</th> </tr> <tr> <th>(mm)</th> <th>長度</th> </tr> <tr> <td>1</td> <td>~ 4</td> <td>-</td> </tr> <tr> <td>4</td> <td>~ 16</td> <td>-</td> </tr> <tr> <td>16</td> <td>~ 63</td> <td>-</td> </tr> <tr> <td>63</td> <td>~ 250</td> <td>-</td> </tr> <tr> <td>250</td> <td>~ 1000</td> <td>-</td> </tr> </table>	公差精度		精級	(mm)	長度	1	~ 4	-	4	~ 16	-	16	~ 63	-	63	~ 250	-	250	~ 1000	-
公差精度		精級																												
(mm)	長度																													
1	~ 4	-																												
4	~ 16	-																												
16	~ 63	-																												
63	~ 250	-																												
250	~ 1000	-																												
006				PG24064WRF-EGAH43Q																										
005				DRAWING NAME :	Design	Crystal	Surface																							
004				JLMD-PG24064WRF-EGAH43Q	Check	Air	Material																							
003				TITLE:	Approve	Liujin	Thickness																							
002				LCD Module Drawing			Quantity																							
001	NEW DRAWING	Crystal	2022/10/25																											
REV	REV BY	REVISER	DATE																											