



- NOTE:
- LCD TYPE:FSTN,Positive,Transflective
 - VIEWING DIRECTION: 6:00 O'CLOCK
 - OPERATING TEMP.: -20°C TO +70°C
 - STORAGE TEMP.: -30°C TO +80°C
 - $a=P2.54 \times 9=22.86 \pm 0.1$; $b=2.54 \pm 0.1$
 - THE TOLERANCE UNLESS CLASSIFIED $\pm 0.3\text{mm}$
 - () REFERENCE DIMENSION ; Component Area
 - THIS PRODUCT CONFORMS ROHS

007				PART NO:	久正光電股份有限公司 POWERTIP TECHNOLOGY CORPORATION				公差精度等級 (mm) 長度 精級	
006				PG320240LRFDDCH57Q						
005				DRAWING NAME:	Design	Clare	(3) Surface Unit MM Scale 1:1 Page 1/1	Material	1 ~ 4	-
004				LMD-PG320240LRFDDCH57Q	Check	Tina			4 ~ 16	-
003				TITLE:	Approve	Bright	Thickness	16 ~ 63	-	
002				LCD MOUDLE DRAWING			Quantity	63 ~ 250	-	
001	NEW DRAWING	Clare	2023/4/18					250 ~ 1000	-	
REV	REV BY	REVISER	DATE							