



- NOTES:
- 1.LCD TYPE: TFT
 - 2.LCD DISPLAY: Normally Black/Transmissive
 - 3.The tolerance unless classified ±0.3mm
 4. Component Area; Insulating Tape; Shading tape; Conductive tape
 - 5.CN1 connector : Starconn 300E40-0010RA-G3 (0.5pitch ; 40pin) or compatible

007				PART NO:	
006				PH128800T006-ZHA	
005				DRAWING NAME :	
004				LMD-PH128800T006-ZHA	
003	Modify Drawing	Clare	2024/3/6	TITLE:	
002	Modify Dimension and Add Conductive tape	Clare	2023/5/12	LCD MODULE DRAWING	
001	NEW DRAWING	Clare	2023/3/23		
REV	REV BY	REVISER	DATE		

		久正光電股份有限公司 POWERTIP TECHNOLOGY CORPORATION													
Design	Clare	(3) Surface	<table border="1"> <thead> <tr> <th>Tolerance Length(Min) (mm)</th> <th>Precision Level</th> </tr> </thead> <tbody> <tr> <td>1 ~ 4</td> <td>-</td> </tr> <tr> <td>4 ~ 16</td> <td>-</td> </tr> <tr> <td>16 ~ 63</td> <td>-</td> </tr> <tr> <td>63 ~ 250</td> <td>-</td> </tr> <tr> <td>250 ~ 1000</td> <td>-</td> </tr> </tbody> </table>	Tolerance Length(Min) (mm)	Precision Level	1 ~ 4	-	4 ~ 16	-	16 ~ 63	-	63 ~ 250	-	250 ~ 1000	-
Tolerance Length(Min) (mm)	Precision Level														
1 ~ 4	-														
4 ~ 16	-														
16 ~ 63	-														
63 ~ 250	-														
250 ~ 1000	-														
Check	Tina	Unit MM													
Approve	Bright	Scale 1:1													
		Page 1/1													